Frontrunner Plus

Internal entrance matting with carpet inserts for maximum moisture removal.

Frontrunner Plus is an absorbent entrance mat specifically designed to not only stop dirt in its tracks, but moisture too.



The mat's aggressive tread pattern scrapes shoes and wheels clean, while heavy-duty absorbent carpet inserts removes and dries any moisture. This reduces cleaning internals, expands the life of your floor finishes and keeps interiors looking stylish for longer. Slip resistant, wheel-proof and heel-proof, Frontrunner Plus is an ideal choice for commercial entrances, especially for businesses and shopping centres with high traffic. Choose from 50 colour and style combinations – you can also add a logo panel for added branding.

Features:

- Diamond cut pattern
- Two layer open-grid construction
- Absorbent carpet inserts
- Close mesh grid
- Comes in 10m (33') rolls or modules



Benefits:

- Slip resistant, high soil removal
- Excellent drainage
- Maximum moisture removal
- Heel-and-wheel proof
- Seamless installation

qsmats - www.qsmats.co.uk

Tel: 01934 864367
Email: info@qsmats.co.uk
Unit 1 Hortswood Farm, Long Lane, Wrington, North Somerset, BS40 5SP.

qsmats commercial matting systems

Frontrunner Plus

Data sheet

Standard sizes:

Product	Frontrunner Plus	Low Profile
Height	14-16mm (9/16" – 5/8")	10.5-12mm (13/32" - 1/2")
Standard roll options	10 x 0.6m (33' x 2')	10 x 0.6m (33' x 2')
	10 x 0.91m (33' x 3')	10 x 0.91m (33' x 3')
	5 x 1.2m (16'6" x 4')	5 x 1.2m (16'6" x 4')
Standard module option	0.8 x 1.2m (2'7" x 4')	
	1 x 1.5m (3'3" x 4'11")	
	1.1 x 2m (3'7" x 6'7")	
Weight	10.5 kg/m2 (2lbs/sq.ft)	8.7kg/m2 (1.6lbs/sq.ft)

Surface modules are supplied with factory fitted PVC ramped edging to four sides

Tolerances:

	Height *(+/- 0.5mm)*	Length *(0+0.3mm)*	Width *(0+2mm)*
Frontrunner Plus	14/16 mm	10 m	60 cm 91 cm
	14/16 mm	5 m	120 cm
Frontrunner Plus Low Profile	10.5/12 mm	10 m	60 cm 91 cm
	10.5/12 mm	5 m	120 cm

All dimensions are nominal

Colours:

Black


Dark grey

Dark brown


Oxford blue


Green

More colours available upon request

Carpets:

Black 608

Dark grey 607


Blue 602

Brown 605


Grey 606

Slate

Basalt

Green


Grey

Sandstone

Frontrunner Plus

Data sheet

PVC grid technical information:

Acoustic	Excellent sound absorption
Chemical	Resistant to most acids, alkalines and oils.
Composition	Flexible Polyvinyl Chloride (PVC)
Environment	We don't use any substances included in the SVHC list under REACH in any of our matting products.
Fire	Frontrunner Plus: EN ISO 13501-1:2007-Cfl-S1, ASTM E648 – Class 1 Frontrunner Plus Low Profile: EN ISO 13501-1:2007-Cfl-S2
Reversion	Thermoplastic shrinkage can result in size reductions up to 2%. This may be accelerated in hot environments.
Slip resistance	ASTM E303 Dry/Wet with lines along–lines across 72-97 / 65-81
Thermal	Designed to function at temperatures from -23°C and up to +60°C. Slight size variation may occur at temperature extremes.
UV light	Resistant to PVC degradation
Warranty	Frontrunner Plus: three years. Frontrunner Plus Low Profile: two years.

Absorbent inserts (Zeno 600 series) technical information:

Wear classification	EN 1307 - 33, Commercial heavy
Pile material	ECONYL®, 100% regenerated polyamide BCF
Tuft base	100% regenerated non woven polyester Colback™
Phthalate Free backing	Waterproof Comfort™ vinyl
Total height	EN 1765 ± 8.7 mm
Pile height	EN 1766 ± 6.7 mm
Total weight	EN 8543 ± 4260 g/m²
Pile yarn weight	± 820 g/m²
Pile density	± 0,127 g/cm³
Fire	EN ISO 13501-1:2007 Cfl-S1
Suitable for castor chairs	EN 985 A, intensive use r=2.8
Colours	10

Installation:

Frontrunner Plus' one-piece construction means installation is simple:

- Cut to fit on site – no special tools or previous site visits needed
- Integrates with all internal floor coverings
- Fits with different well depths
- Contours to the floor

Cleaning:

Keeping Frontrunner Plus looking good is easy:

- Reduces cleaning intervals
- Simply roll or lift to clean
- No special tools needed
- Easy to vacuum

Frontrunner Plus

Data sheet

Ancillaries:

> For surface mounted installations

PVC edging (H: 14mm, W: 60mm)



Supplied in rolls of 10.1m (33') length with cold welding paste. Comes in black, dark grey, dark brown, holly green, Oxford blue, yellow. Size: 14mm x 60mm x 10.1m (9/16" x 2 1/2" x 33')

PVC edging (H: 14mm, W: 100mm)



Supplied in rolls of 10.1m (33') length with cold welding paste. Comes in black, dark grey and yellow. Size: 14mm x 100mm x 10.1m (9/16" x 3 3/4" x 33')

PVC snap track (H: 14mm)



Two-part snap track that can be welded together to join rolls end-to-end or side-to-side to cover large areas. Supplied with cold welding paste. Comes in black and dark grey. Size: 14mm x 2.5m (9/16" x 8'2").

Aluminium edging (H: 15mm)



Supplied in sections of 2m (6'6") length with fixing screws and plugs. Comes in anodised aluminium and powder coated yellow. Size: 15mm x 45mm x 2m (9/16" x 1 13 /16" x 6'6")

Connector clips: side-to-side (H: 14mm)

For joining sections of low profile matting together side-to-side. Supplied in packs of 10

> For recessed installations

R frame (H: 14mm)

You'll need these to secure the matting on the left-to-right edges. Supplied in sections of 3m (10') length with fixing screws and plugs. Comes in anodised aluminium, powder coated dark grey and black. Size: 14mm x 12mm (9/16" x 15/32")

J frame (H: 18mm)



Installing Frontrunner against a wall? You'll need a J frame to secure the matting on the left-to-right edges. Supplied in sections of 3m (10') length with fixing screws and plugs. Comes in dark grey and black. Size: 18mm x 60mm (11/16" x 2 3/8")

Frontrunner Plus

Data sheet

Ancillaries:

T frame (H: 14mm)

You can use a T frame (27mm) to divide the matting into sections left-to-right – this makes it easier to lift and clean. Supplied in sections of 3m (10') length with fixing screws and plugs. Comes in anodised aluminium, powder coated dark grey and black

TL frame (H: 14mm)



You can use a T/L frame (55mm) to divide the matting into sections left-to-right – this makes it easier to lift and clean. Supplied in sections of 3m (10') length with fixing screws and plugs. Comes in anodised aluminium

H section (H: 14mm)

If the front-to-back dimension of the mat well is greater than the final width of your matting, you may need a H section to secure the different sections together. Supplied in sections of 3m (10') length, with fixing screws and plugs. Comes in black, with mat insert colour specified. Size: 14mm x 13mm (9/16" x 1/2")

U section (H: 14mm)



If the front-to-back dimension of the mat well is greater than the final width of your matting, you may need a U section to secure the different sections together. Supplied in sections of 3m (10') length, with fixing screws and plugs. Comes in anodised aluminium, powder coated dark grey and black. Size: 14mm x 19mm (9/16" x 3/4")

L frame (H: 15mm)

Installing around a circular door or non rectangular space? You'll need a L frame to secure the matting. Size: 15mm x 2.7m length (5/18" x 8')

> For surface mounted installations: Low profile

PVC edging (H: 10mm, W: 50mm)



Supplied in rolls of 10.1m (33') length with cold welding paste. Comes in black and dark grey. Size: 10mm x 50mm x 10.1m (3/8" x 2" x 33')

PVC snap track (H: 10.5mm)



Two-part snap track that can be welded together to join rolls end-to-end or side-to-side to cover large areas. Supplied with cold welding paste. Comes in dark grey. Size: 10.5mm x 2.5m (13/32" x 8'2")

Frontrunner Plus

Data sheet

Ancillaries:

Connector clips: side-to-side (H: 10mm)



For joining sections of low profile matting together side-to-side. Supplied in packs of 10

> For recessed installations: Low profile

R frame (H: 10mm)

You'll need these to secure the matting on the left-to-right edges. Supplied in sections of 3m (10') length with fixing screws and plugs. Comes in anodised aluminium, powder coated dark grey and black. Size: 10mm x 12mm (3/8" x 15/32")

U section (H: 10mm)



If the front-to-back dimension of the mat well is greater than the final width of your matting, you may need a U section to secure the different sections together. Supplied in sections of 3m (10') length, with fixing screws and plugs. Comes in anodised aluminium, powder coated dark grey and black. Size: 10mm x 18mm (3/8" x 11/16")

H section (H: 10mm)

If the front-to-back dimension of the mat well is greater than the final width of your matting, you may need a H section to secure the different sections together. Supplied in sections of 3m (10') length, with fixing screws and plugs. Comes in black, with mat insert colour specified. Size: 10mm x 13mm (3/8" x 1/2")

Z frame (H: 10mm)

Installing matting next to ceramic tiles? You'll need a Z frame to secure the matting. Supplied in sections of 3.6m (11') length with fixing screws and plugs. Comes in anodised aluminium, powder coated dark grey and black. Size: 10mm x 24mm (3/8" x 15/16")